
PTZ CAM SPECIFICATIONS

Image Sensor

680K pixels (340K effective)

Zoom

26x optical/12x digital/312x combined

Minimum Object Illumination

1 lux (1/30 shutter speed)

Pan Angle Range

±100° (Standard) / ±170° (Reverse)

Tilt Angle Range

+90°/-30° (Standard) / +10°/-90° (Reverse)

Network

Ethernet 10M/100M, auto negotiation

Protocol

TCP/IP, HTTP, DHCP, FTP, NTP, DDNS, SMTP

Capture Frame Rate

30 fps (640 x 480)

Video Capture Sizes

160 x 120, 320 x 240, 640 x 480

Video Compression Method

Motion-JPEG (video), JPEG (still images)

Simultaneous Client Access

50 (max.)

Compatible Viewers

Network Video Recording Software VK-64, Viewer for Java, Viewer for PC, Admin Viewer, WebView
Livescope MV Ver. 2.1/ 2.1 LE

Server Functions

WWW, FTP

Video Transmission Rate

0.1 to 30 fps (variable)

Connection Limitation

Using software management tools

Setting for Camera

Using software management tools

Control Privileges View Restriction

Using software management tools

Home Position Function

Using software management tools

Camera Angle Presets

20 positions

External Device Inpts/Outputs

2/3 (optional)

Recording Capacity

Approx. 15MB (JPEG)

Picture Recording

Schedule/Sensor/Motion Detection

Video Input

Composite

Audio

Client PC to camera

Display and Management of Stored Images

VB Collector, WebView Livescope MV Ver. 2.1

Operating Environment

32-104°F (0-40°C) 20-85% RH (non-condensing)

Power Supply

AC adapter (included) DC13V (11.5-14V)

Power Consumption

9.7W or less

Dimensions (W x D x H)

VB-C50i: 4.1" x 5.1" x 4.3" (104.6 x 130.3 x 109.7mm) (excluding attachments)

VB-C50iR: 5.4" x 5.1" x 4.4" (136 x 130.3 x 110.6mm) (excluding attachments)

Weight

VB-C50i: 1.37 lbs. (620g) / VB-C50iR: 1.54 lbs. (700g)

PTZ CAM SPECIFICATIONS

www.siteisight.com Copyright 2007